



PLASTIC FITTINGS WITH METAL CABLE GLAND IP 68/IP 69K (PG THREAD)

Material: fitting body in polyamide 6, internal gasket in TPE, body of the cable gland and thread in nickel-plated brass.

Color: black.

Use temperature: -50°C / +120°C

IP protection: IP 68, IP 69.

Flammability: flame retardant and self-extinguishing UL94-V0 (polyamide 6).

Regulations and Certifications: CE, VDE (EN/IEC 61386-23), DIN EN 45545-2 HL3, NFPA 130 (ASTM E162/E662, SMP 800-C), LLOYD'S REGISTER, c-UR-us (UL 1696 / CSA 22.2; file n. E86359, per le misure AD13-AD54,5), JRMA.

Features: they ensure perfect mechanical, tear-proof and anti-vibration resistance.

They guarantee IP 68 and IP 69K protection for maximum pressurized water tightness. The integrated cable gland, with internal sealing rubber, allows a waterproof and tear-resistant cable locking. The metal thread gives the fittings maximum tightness when tightened whether they are mounted with the lock nut or mounted directly on the structure. The thread is internally coated in plastic to give maximum insulation to the cables. They are available with PG, Metric thread. Resistance to oils, gasoline and in particular to acids and solvents. They do not contain cadmium, silicone or halogens.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	OD tube AD	thread pitch	thread value	Ø est. min - max cable mm	ØA mm	ØB mm	F mm	H mm	key mm	pack pcs.
RQGKZ-P 7 AD10 NERI	10	PG	7	3 - 6	6,8	20,5	5	50	18/14	50
RQGKZ-P 9 AD13 NERI	13	PG	9	4 - 7,5	8,5	24	6	56,5	22/17	50
RQGKZ-P 11 AD15,8 NERI	15,8	PG	11	4 - 9,5	10,5	27	6	57	25/20	50
RQGKZ-P 16 AD21,2 NERI	21,2	PG	16	9 - 13	14,8	33	6,5	65	31/24	25
RQGKZ-P 21 AD28,5 NERI	28,5	PG	21	11,5 - 17	18,5	41	7	71	39/30	25
RQGKZ-P 29 AD34,5 NERI	34,5	PG	29	19 - 23	25,5	48,5	8	75	46/40	25
RQGKZ-P 36 AD42,5 NERI	42,5	PG	36	25 - 33	34,5	58	9	103	55/50	10

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





RQ GKZ-P	54,5	PG	48	35 - 43	44	68	10	120	65/64	10
48 AD54,5										
NERI										

N.B.: se in tabella, nella colonna "chiave", vi sono due dimensioni separate da " / " (esempio: 22/17), la prima dimensione corrisponde al CORPO del raccordo, mentre la seconda alla TESTA filettata. In caso di dimensione unica, essa corrisponde ad entrambe le parti.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

