



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

PLASTIC FITTINGS WITH INTERNAL METAL THREAD IP 68/IP 69K (PG THREAD)

ITEM: RQ GK2-P 13,5 AD18,5 NERI

Codice EZ: request the code from our sales office, **PLASTIC Flexa code:** 15020075213.

Material: polyamide 6, internal gasket in TPE, internal thread in nickel-plated brass.

Color: black.

Use temperature: -40°C / +115°C

IP protection: IP 68 according to EN 60529/IEC 60529 specifications and IP 69K according to DIN 40050 T.9 specifications.

Flammability: flame retardant and self-extinguishing UL94-V0 (polyamide 6).

Regulations and Certifications: VDE (EN/IEC 61386-23), c-CSA-us (UL 1696, valid for measurements AD21.2 to AD54.5), DB (DIN 5510 2, S1), SNCF (NFF 16-101/102 , I3/F2), EN 45545-2 (HL 2), LLOYD'S REGISTER OF SHIPPING (suitability for use in naval and offshore applications).

Features: they ensure excellent mechanical, tear-proof and anti-vibration resistance. They guarantee IP 68 and IP 69K protection for maximum pressurized water tightness. The metal thread gives the fittings greater resistance to mechanical stress and maximum tightness when tightening. They are available with PG, Metric internal thread. Resistance to oils, gasoline and in particular to acids and solvents. They do not contain cadmium, silicone or halogens.

ITEM	OD tube AD	thread pitch	thread value	ØA mm	ØB mm	F mm	H mm	key mm	pack pcs.
RQ GK2-P 13,5 AD18,5 NERI	18,5	PG	13,5	12,5	29	9,5	45	26	50

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

