



RUBBER SLEEVES - "HELAVIA" SERIES - ITEM: A1K GIALLI

Codice EZ: 106958, RUBBER SES-Sterling code: 02010081004.

Material: neoprene 3490.

Color: black, white, blue, green, yellow, orange, brown, red, purple, gray, pink, light blue or yellow/green.

Use temperature: -30°C / +90°C

Flammability: flame retardant and self-extinguishing UL94-V0.

Features: the sleeves are very elastic and are the ideal solution for the insulation and protection of the ends of the conductors from dirt, corrosion and friction. They have a medium resistance to oils, petrol, ozone and aging. They can also be used as a cable marking system. The assembly of the sleeves on the conductors is carried out using the 3-pronged pliers and is facilitated by the internal lubrication. The sleeves with internal diameter from 10 mm onwards are not internally lubricated; therefore, to facilitate the assembly of these on the calipers, it is advisable to use the lubricant LUB 2.

On request: for quantities, special "antistatic" conductive sleeves can be supplied produced in a nitrile-based rubber with a hardness of 60 Shore A, with a transversal resistivity of the order of 10 6 Ohm.cm, with a good chemical resistance to oils and with a temperature of use -25°C / +100°C.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	Ø est. min - max cable mm	ØA mm	L mm	S mm	pack pcs.
A1K GIALLI*	yellow	2,5 - 5,5	2,5	25	0,9	1000

* Sleeve with increased wall thickness.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

