



PLASTIC SPACERS FOR PCB BUTTON WITH HOOK

Material: polyamide 66.

Color: natural.

Use temperature: max +85°C

Features: these spacers are mounted under pressure from underneath the frame, making them pass through both holes in the walls. They are characterized by the convex head and are distinguished by the locking hook with reduced dimensions. On request: they can be made of flame-retardant and self-extinguishing UL94-V0 polyamide resistant up to +105°C.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	H mm	H1 mm	H2 mm	super thick frame. / infer.	Top mounting hole ø mm	Lower mounting hole ø mm	pack pcs.
DR-BOC 1	6	4	1,9	1,6 / 1,6	4	5,4	1000
DR-BOC 2	6	4	1,9	1,6 / 2	4	5,4	1000
DR-BOC 3	8	4	1,9	1,6 / 1,6	4	5,4	1000
DR-BOC 4	8	4	1,9	1,6 / 2	4	5,4	1000
DR-BOC 5	10	4	1,9	1,6 / 1,6	4	5,4	1000
DR-BOC 6	10	4	1,9	1,6 / 2	4	5,4	1000
DR-BOC 7	12	4	1,9	1,6 / 1,6	4	5,4	1000
DR-BOC 8	12	4	1,9	1,6 / 2	4	5,4	1000
DR-BOC 14.1,6	14	4	1,9	1,6 / 1,6	4	5,4	1000
DR-BOC 14.2	14	4	1,9	1,6 / 2	4	5,4	1000

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

