



PLASTIC SPACERS FOR "MALE-MALE" PCB WITH TWO HOOKS AND TWO ARCHES

Material: UL94-V2 flame-retardant polyamide 66 (PA 66-V2) and UL94-V0 flame-retardant polyamide 66 (PA 66-V0).

Color: natural (PA 66-V2), white (PA 66-V0).

Use temperature: max +85°C (PA 66-V2), max +105°C (PA 66-V0).

Flammability: flame-retardant and self-extinguishing UL94-V2 (PA 66-V2), flame-retardant and self-extinguishing UL94-V0 (PA 66-V0).

Features: these spacers have two locking hooks.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	Material	H mm	super thick frame. / infer.	Top mounting hole ø mm	Lower mounting hole ø mm	pack pcs.
DBB 1	natural	PA 66-V2	4,8	0,8-2 / 0,8-2	4	4	1000
DBB 1A	White	PA 66-V0	4,8	0,8-2 / 0,8-2	4	4	1000
DBB 2	natural	PA 66-V2	6,4	0,8-2 / 0,8-2	4	4	1000
DBB 2A	White	PA 66-V0	6,4	0,8-2 / 0,8-2	4	4	1000
DBB 3	natural	PA 66-V2	9,5	0,8-2 / 0,8-2	4	4	1000
DBB 3A	White	PA 66-V0	9,5	0,8-2 / 0,8-2	4	4	1000
DBB 4	natural	PA 66-V2	12,7	0,8-2 / 0,8-2	4	4	1000
DBB 4A	White	PA 66-V0	12,7	0,8-2 / 0,8-2	4	4	1000
DBB 5	natural	PA 66-V2	15,9	0,8-2 / 0,8-2	4	4	1000
DBB 5A	White	PA 66-V0	15,9	0,8-2 / 0,8-2	4	4	1000
DBB 6	natural	PA 66-V2	19,1	0,8-2 / 0,8-2	4	4	1000
DBB 6A	White	PA 66-V0	19,1	0,8-2 / 0,8-2	4	4	1000
DBB 7	natural	PA 66-V2	22,2	0,8-2 / 0,8-2	4	4	1000
DBB 7A	White	PA 66-V0	22,2	0,8-2 / 0,8-2	4	4	1000

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

