



PLASTIC SPACERS FOR PCB "MALE-MALE" WITH HOOK AND LOCKING TOOTH

Material: UL94-V2 flame-retardant polyamide 66 (PA 66-V2) and UL94-V0 flame-retardant polyamide 66 (PA 66-V0).

Color: natural (PA 66-V2), white (PA 66-V0).

Use temperature: max +85°C (PA 66-V2), max +105°C (PA 66-V0).

Flammability: flame-retardant and self-extinguishing UL94-V2 (PA 66-V2), flame-retardant and self-extinguishing UL94-V0 (PA 66-V0).

Features: these spacers are characterized by the hook and the locking tooth.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	Material	H mm	super thick frame. / infer.	Top mounting hole ø mm	Lower mounting hole ø mm	pack pcs.
DRD 1	natural	PA 66-V2	4,8	1,6 / 0,8-2	4	4,8	1000
DRD 2	natural	PA 66-V2	6,4	1,6 / 0,8-2	4	4,8	1000
DRD 2A	White	PA 66-V0	6,4	1,6 / 0,8-2	4	4,8	1000
DRD 07,9	natural	PA 66-V2	7,9	1,6 / 0,8-2	4	4,8	1000
DRD 07,9A	White	PA 66-V0	7,9	1,6 / 0,8-2	4	4,8	1000
DRD 3	natural	PA 66-V2	9,5	1,6 / 0,8-2	4	4,8	1000
DRD 3A	White	PA 66-V0	9,5	1,6 / 0,8-2	4	4,8	1000
DRD 4	natural	PA 66-V2	11,1	1,6 / 0,8-2	4	4,8	1000
DRD 4A	White	PA 66-V0	11,1	1,6 / 0,8-2	4	4,8	1000
DRD 5	natural	PA 66-V2	12,7	1,6 / 0,8-2	4	4,8	1000
DRD 5A	White	PA 66-V0	12,7	1,6 / 0,8-2	4	4,8	1000
DRD 6	natural	PA 66-V2	15,9	1,6 / 0,8-2	4	4,8	1000
DRD 6A	White	PA 66-V0	15,9	1,6 / 0,8-2	4	4,8	1000
DRD 7	natural	PA 66-V2	19,1	1,6 / 0,8-2	4	4,8	1000
DRD 8A	White	PA 66-V0	22,2	1,6 / 0,8-2	4	4,8	1000
DRD 9A	White	PA 66-V0	25,4	1,6 / 0,8-2	4	4,8	1000
DRD 10	natural	PA 66-V2	28,6	1,6 / 0,8-2	4	4,8	1000
DRD 10A	White	PA 66-V0	28,6	1,6 / 0,8-2	4	4,8	1000
DRD 11	natural	PA 66-V2	31,7	1,6 / 0,8-2	4	4,8	1000
DRD 11A	White	PA 66-V0	31,7	1,6 / 0,8-2	4	4,8	1000
DRD 12	natural	PA 66-V2	34,9	1,6 / 0,8-2	4	4,8	1000

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993