




## PLASTIC SPACERS FOR "MALE-MALE" PCB WITH HOOK AND LOCKING TOOTH

### ITEM: DRC 07,9A

**Codice EZ:** request the code from our sales office

Material: UL94-V2 flame-retardant polyamide 66 (PA 66-V2) and UL94-V0 flame-retardant polyamide 66 (PA 66-V0)

Color: natural (PA 66-V2), white (PA 66-V0).

Use temperature: max +85°C (PA 66-V2), max +105°C (PA 66-V0).

Flammability: flame-retardant and self-extinguishing UL94-V2 (PA 66-V2), flame-retardant and self-extinguishing UL94-V0 (PA 66-V0).

Features: these spacers have a hook and a locking tooth.

On request: DRA type spacers can be supplied in a UL94-V0 flame-resistant thermoplastic material resistant up to -40°C and +200°C, in black color.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

| ITEM        | Color | Material | H mm | super thick<br>frame. / infer. | Top mounting<br>hole ø mm | Lower mounting<br>hole ø mm | pack pcs. |
|-------------|-------|----------|------|--------------------------------|---------------------------|-----------------------------|-----------|
| DRC 07,9A** | White | PA 66-V0 | 7,9  | 2,4 / 0,8-2                    | 4                         | 4,8                         | 1000      |

\* These spacers can be supplied with the same dimensions, but for less than 0.2-1.4mm wall thickness. Furthermore, they can also be supplied in metric sizes, i.e. with the following heights (A): 6, 8, 10, 12, 14, 16 mm. \*\* These spacers can be supplied with the same dimensions, but for wall thicknesses of less than 2-3.6mm.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

## ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

