

MDU

## PLASTIC SPACERS FOR PCB "MALE-MALE" WITH TWO HOOKS - "MINI" SERIES

**ITEM: MDU-V0 2546.3,6-1,6 03  
BIANCHI**

**Codice EZ:** request the code from our sales office


Material: UL94-V2 flame-retardant polyamide 66 (PA 66-V2), UL94-V0 flame-retardant polyamide 66 (PA 66-V0).

Color: natural, white.

Use temperature: -20°C / +85°C (PA 66-V2), -40°C / +105°C (PA 66-V0)

Flammability: flame-retardant and self-extinguishing UL94-V2 (PA 66-V2), flame-retardant and self-extinguishing UL94-V0 (PA 66-V0).

Features: these spacers have a reduced body and are characterized by two locking hooks. Both mounting holes have a tolerance of +/- 0.08mm and the height H has a tolerance of +/- 0.4mm.



MDUD

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

| ITEM                                     | Color | Material | Lower mounting hole Ø mm | lower frame thickness mm | Top mounting hole Ø mm | upper frame thickness mm | ØB mm | H mm | H1 mm | L1 mm | L2 mm | pack pcs. |
|------------------------------------------|-------|----------|--------------------------|--------------------------|------------------------|--------------------------|-------|------|-------|-------|-------|-----------|
| MDU-V0<br>2546.3,6-<br>1,6 03<br>BIANCHI | White | PA 66-V0 | 2,5                      | 3,6                      | 2,5                    | 1,6                      | 4,6   | 3    | 2     | 3     | 2,1   | 1000      |

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

### ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

