



PLASTIC SPACERS FOR "MALE-MALE" PCB WITH TWO HOOKS AND CYLINDRICAL BODY - "MINI" SERIES

**ITEM: MUC-L-V0 3246.1,57 3,2
BIANCHI**

Codice EZ: request the code from our sales office

Material: UL94-V2 flame-retardant polyamide 66 (PA 66-V2), UL94-V0 flame-retardant polyamide 66 (PA 66-V0).

Color: natural, white.

Use temperature: -20°C / +85°C (PA 66-V2), -40°C / +105°C (PA 66-V0)

Flammability: flame-retardant and self-extinguishing UL94-V2 (PA 66-V2), flame-retardant and self-extinguishing UL94-V0 (PA 66-V0).

Features: these spacers have a body with reduced dimensions and are characterized by a cylindrical body and two locking hooks. Both mounting holes have a tolerance of +/- 0.08mm and the height H has a tolerance of +/- 0.4mm.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	Material	Top mounting hole ø mm	upper frame thickness mm	Lower mounting hole ø mm	lower frame thickness mm	B mm	H mm	H3 mm	L1 mm	pack pcs.
MUC-L-V0 3246.1,57 3,2 BIANCHI	White	PA 66-V0	3,18	1,57	3,18	1,57	4,6	3,2	3,7	3,8	1000

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

