



## PLASTIC SPACERS FOR "MALE-MALE" PCB WITH TWO HOOKS AND CYLINDRICAL BODY - "MINI" SERIES

**ITEM: MUC-L-V0 3946.1,57 12,7  
BIANCHI**

**Codice EZ: request the code from our sales office**

Material: UL94-V2 flame-retardant polyamide 66 (PA 66-V2), UL94-V0 flame-retardant polyamide 66 (PA 66-V0).

Color: natural, white.

Use temperature: -20°C / +85°C (PA 66-V2), -40°C / +105°C (PA 66-V0)

Flammability: flame-retardant and self-extinguishing UL94-V2 (PA 66-V2),  
flame-retardant and self-extinguishing UL94-V0 (PA 66-V0).

Features: these spacers have a body with reduced dimensions and are characterized by a cylindrical body and two locking hooks. Both mounting holes have a tolerance of +/- 0.08mm and the height H has a tolerance of +/- 0.4mm.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

| ITEM                                     | Color | Material | Top<br>mounting<br>hole ø mm | upper<br>frame<br>thickness<br>mm | Lower<br>mounting<br>hole ø mm | lower<br>frame<br>thickness<br>mm | B mm | H mm | H3 mm | L1 mm | pack pcs. |
|------------------------------------------|-------|----------|------------------------------|-----------------------------------|--------------------------------|-----------------------------------|------|------|-------|-------|-----------|
| MUC-L-V0<br>3946.1,57<br>12,7<br>BIANCHI | White | PA 66-V0 | 3,86                         | 1,57                              | 3,86                           | 1,57                              | 4,6  | 12,7 | 3,6   | 4,1   | 1000      |

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

### ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

