



PLASTIC SPACERS FOR PCB "MALE-MALE" WITH TWO HOOKS AND TWO BOWS - "MINI" SERIES

**ITEM: MGA-V0 3244.1,98 12,7
BIANCHI**

Codice EZ: request the code from our sales office

Material: UL94-V2 flame-retardant polyamide 66 (PA 66-V2), UL94-V0 flame-retardant polyamide 66 (PA 66-V0).

Color: natural, white.

Use temperature: -20°C / +85°C (PA 66-V2), -40°C / +105°C (PA 66-V0)

Flammability: flame-retardant and self-extinguishing UL94-V2 (PA 66-V2), flame-retardant and self-extinguishing UL94-V0 (PA 66-V0).

Features: these spacers have a reduced body and are characterized by locking hooks with two arches. Both mounting holes have a tolerance of +/- 0.05mm and the height H has a tolerance of +/- 0.4mm.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	Material	Top mounting hole Ø mm	upper frame thickness mm	Lower mounting hole Ø mm	lower frame thickness mm	ØB mm	H mm	H1 mm	L1 mm	pack pcs.
MGA-V0 3244.1,98 12,7 BIANCHI	White	PA 66-V0	3,18	0,79 - 1,98	3,18	0,79 - 1,98	4,4	12,7	4	4,18	1000

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

