

PLASTIC SPACERS FOR PCB "MALE-MALE" WITH HOOK AND LOCKING TOOTH - "MINI" SERIES

ITEM: MCO 3244.1,57 3,2 NATURALI

Codice EZ: request the code from our sales office


Material: polyamide 66.

Color: natural.

Use temperature: -20°C / +85°C

Flammability: flame retardant and self-extinguishing UL94-V2.

Features: these spacers have a reduced body and are characterized by the hook and the locking tooth. The MCO2 spacer is distinguished by its conical base. Both mounting holes have a tolerance of +/- 0.08mm and the height H has a tolerance of +/- 0.4mm.



MCO2

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Top mounting hole Ø mm	upper frame thickness mm	Lower mounting hole Ø mm	lower frame thickness mm	B mm	H mm	H2 mm	H3 mm	H4 mm	L1 mm	L2 mm	pack pcs.
MCO 3244.1,57 3,2 NATURAL I	3,18	1,57	3,18	1,57	4,4	3,2	2,9	8,7	-	4,4	3,7	1000

* This spacer has a conical base.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

