

fig. A




fig. B

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

## PLASTIC SPACERS FOR "MALE-MALE" PCB WITH HOOK AND TENSION TOOTH - "MINI" SERIES

### ITEM: MDR-V0 38636.1,6 3,2

**Codice EZ:** request the code from our sales office

Material: UL94-V2 flame-retardant polyamide 66 (PA 66-V2), UL94-V0 flame-retardant polyamide 66 (PA 66-V0).

Color: natural, white.

Use temperature: -20°C / +85°C (PA 66-V2), -40°C / +105°C (PA 66-V0).

Flammability: flame-retardant and self-extinguishing UL94-V2 (PA 66-V2), flame-retardant and self-extinguishing UL94-V0 (PA 66-V0).

Features: these spacers have a reduced body and are characterized by the hook and the tension tooth. Both mounting holes have a tolerance of +/- 0.08mm and the height H has a tolerance of +/- 0.4mm.

| ITEM                        | Color | Material | specific | Lower<br>mountin<br>g hole ø<br>mm | Top<br>mountin<br>g hole ø<br>mm | lower<br>frame<br>thicknes<br>s mm | upper<br>frame<br>thicknes<br>s mm | H mm | H3 mm | H4 mm | L1 mm | L2 mm | pack<br>pcs. |
|-----------------------------|-------|----------|----------|------------------------------------|----------------------------------|------------------------------------|------------------------------------|------|-------|-------|-------|-------|--------------|
| MDR-V0<br>38636.1,<br>6 3,2 | White | PA 66-V0 | fig. B.  | 3,86                               | 3,86                             | 1,6                                | 1,6                                | 3,2  | 3,6   | 3,6   | 4,05  | 4,2   | 1000         |

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

#### ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

