

fig. A




fig. B

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

PLASTIC SPACERS FOR "MALE-MALE" PCB WITH HOOK AND TENSION TOOTH - "MINI" SERIES

ITEM: MDR-V0 38636.1,6 6,4

Codice EZ: request the code from our sales office

Material: UL94-V2 flame-retardant polyamide 66 (PA 66-V2), UL94-V0 flame-retardant polyamide 66 (PA 66-V0).

Color: natural, white.

Use temperature: -20°C / +85°C (PA 66-V2), -40°C / +105°C (PA 66-V0).

Flammability: flame-retardant and self-extinguishing UL94-V2 (PA 66-V2), flame-retardant and self-extinguishing UL94-V0 (PA 66-V0).

Features: these spacers have a reduced body and are characterized by the hook and the tension tooth. Both mounting holes have a tolerance of +/- 0.08mm and the height H has a tolerance of +/- 0.4mm.

ITEM	Color	Material	specific	Lower mountin g hole ø mm	Top mountin g hole ø mm	lower frame thicknes s mm	upper frame thicknes s mm	H mm	H3 mm	H4 mm	L1 mm	L2 mm	pack pcs.
MDR-V0 38636.1, 6 6,4	White	PA 66-V0	fig. B.	3,86	3,86	1,6	1,6	6,4	3,6	3,6	4,05	4,2	1000

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

