




PLASTIC SPACERS FOR "MALE-MALE" PCB WITH HOOK AND TENSION TOOTH

**ITEM: DDT 47-4071.1,98-1,57 6,4
NATURALI**

Codice EZ: request the code from our sales office

Material: polyamide 66.

Color: natural.

Use temperature: -20°C / +85°C

Flammability: flame retardant and self-extinguishing UL94-V2.

Features: these spacers are characterized by the locking hook and the tension tooth.

Both mounting holes have a tolerance of +/- 0.08mm and the height H has a tolerance of +/- 0.4mm.

On request: they can be supplied in UL94-V0 flame retardant polyamide 66 (-40°C / +105°C).

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Top mounting hole ø mm	upper frame thickness mm	Lower mounting hole ø mm	lower frame thickness mm	B mm	H mm	H2 mm	H3 mm	L1 mm	L2 mm	pack pcs.
DDT 47-4071.1, 98-1,57 6,4 NATURALI	4	1,57	4,75	0,79 - 1,98	7,1	6,4	5,4	10,2	4,5	5,9	1000

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

