



PLASTIC SPACERS FOR "MALE-MALE" THREADED PCB WITH HOOK (METRIC THREAD)

ITEM: SDA 25M3.1,6 7,9 NERI

Codice EZ: request the code from our sales office

Material: UL94-V2 flame-retardant polyamide 66 (PA 66-V2), UL94-V0 flame-retardant polyamide 66 (PA 66-V0).

Color: natural, black, white.

Use temperature: -20°C / +85°C (PA 66-V2), -40°C / +105°C (PA 66-V0)

Flammability: flame-retardant and self-extinguishing UL94-V2 (PA 66-V2), flame-retardant and self-extinguishing UL94-V0 (PA 66-V0).

Features: these spacers are characterized by the locking hook and the male thread.

The top mounting hole has a tolerance of +/- 0.05mm.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	Material	Top mountin g hole ø mm	upper frame thicknes s mm	thread pitch F1	thread value F1	H mm	B mm	H1 mm	H3 mm	H4 mm	L1 mm	pack pcs.
SDA 25M3.1,6 7,9 NERI	black	PA 66-V2	2,5	1,6	Metric	3	7,9	4,8	2	3,7	6,4	3	1000

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

