



## PLASTIC SPACERS FOR "MALE-MALE" THREADED PCB WITH HOOK (METRIC THREAD)

### ITEM: SDA-V0 25M3.1,6 7,9 BIANCHI

**Codice EZ:** request the code from our sales office

Material: UL94-V2 flame-retardant polyamide 66 (PA 66-V2), UL94-V0 flame-retardant polyamide 66 (PA 66-V0).

Color: natural, black, white.

Use temperature: -20°C / +85°C (PA 66-V2), -40°C / +105°C (PA 66-V0)

Flammability: flame-retardant and self-extinguishing UL94-V2 (PA 66-V2), flame-retardant and self-extinguishing UL94-V0 (PA 66-V0).

Features: these spacers are characterized by the locking hook and the male thread.

The top mounting hole has a tolerance of +/- 0.05mm.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

| ITEM                                 | Color | Material | Top<br>mountin<br>g hole ø<br>mm | upper<br>frame<br>thicknes<br>s mm | thread<br>pitch F1 | thread<br>value F1 | H mm | B mm | H1 mm | H3 mm | H4 mm | L1 mm | pack<br>pcs. |
|--------------------------------------|-------|----------|----------------------------------|------------------------------------|--------------------|--------------------|------|------|-------|-------|-------|-------|--------------|
| SDA-V0<br>25M3.1,6<br>7,9<br>BIANCHI | White | PA 66-V0 | 2,5                              | 1,6                                | Metric             | 3                  | 7,9  | 4,8  | 2     | 3,7   | 6,4   | 3     | 1000         |

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

#### ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

