



PLASTIC SPACERS FOR "MALE-MALE" THREADED PCB WITH LOCKING TOOTH AND CROSS BODY (UNC THREAD)

**ITEM: SDM 40U8-32.1,57 28,6
NATURALI**

Codice EZ: request the code from our sales office

Material: UL94-V2 flame-retardant polyamide 66 (PA 66-V2), UL94-V0 flame-retardant polyamide 66 (PA 66-V0).

Color: natural, white.

Use temperature: -20°C / +85°C (PA 66-V2), -40°C / +105°C (PA 66-V0)

Flammability: flame-retardant and self-extinguishing UL94-V2 (PA 66-V2), flame-retardant and self-extinguishing UL94-V0 (PA 66-V0).

Features: these spacers are characterized by the locking tooth, the cross body and the hexagonal bases. The top mounting hole has a tolerance of +/- 0.08mm and the height H has a tolerance of +/- 0.4mm.

On request: for quantity, they can be made in black in both materials.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	Material	Top mounting hole ø mm	upper frame thickness mm	thread pitch F1	thread value F1	B mm	H mm	H3 mm	H4 mm	pack pcs.
SDM 40U8-32.1, 57 28,6 NATURALI	natural	PA 66-V2	4	1,57	A C	8 - 32	8	28,6	10,2	6,4	1000

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

