



PLASTIC SPACERS FOR "MALE-MALE" THREADED PCB WITH LOCKING TOOTH, CROSS BODY AND LONG THREAD (UNC THREAD)

**ITEM: SDML 40U6-32.1,57 12,7
NATURALI**

Codice EZ: request the code from our sales office

Material: polyamide 66.

Color: natural.

Use temperature: -20°C / +85°C

Flammability: flame retardant and self-extinguishing UL94-V2.

Features: these spacers are characterized by the locking tooth, the cross body and the cylindrical bases. The top mounting hole has a tolerance of +/- 0.08mm and the height H has a tolerance of +/- 0.4mm.

On request: for quantity, they can be made in black color.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Top mounting hole Ø mm	upper frame thickness mm	thread pitch F1	thread value F1	ØB mm	H mm	H3 mm	H4 mm	pack pcs.
SDML 40U6-32.1,57 12,7 NATURALI	4	1,57	A C	6 - 32	7,1	12,7	10,2	7,6	1000

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

