

fig. A

## "FEMALE-FEMALE" THREADED CYLINDRICAL SPACERS IN POM WITH GLASS FIBER

### ITEM: FF01 R 2560 44

**Codice EZ:** request the code from our sales office

Material: POM (polyoxymethylene) reinforced with glass fiber (30%).

Color: White.

Use temperature: max +100°C

Flammability: UL94-HB flame retardant (index refers to the material).

Features: POM is characterized by good mechanical strength, high hardness and rigidity. In the table, if the P1 value coincides with the L value, the spacer has a single thread along the entire axis.

On request: these spacers can be made in intermediate lengths (even decimal), which are included between the minimum and maximum length.




fig. B




fig. C

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

| ITEM              | specific | thread pitch<br>F1 | thread value<br>F1 | thread pitch<br>F2 | thread value<br>F2 | ØB mm | L mm | P1 mm | pack pcs. |
|-------------------|----------|--------------------|--------------------|--------------------|--------------------|-------|------|-------|-----------|
| FF01 R 2560<br>44 | fig. B.  | Metric             | 2,5                | Metric             | 2,5                | 6     | 44   | 10    | 100       |

\* Item with through hole and fully threaded.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

#### ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993