

fig. A

"FEMALE-FEMALE" THREADED CYLINDRICAL SPACERS IN POM WITH GLASS FIBER

ITEM: FF01 R 3060 60

Codice EZ: 350139

Material: POM (polyoxymethylene) reinforced with glass fiber (30%).

Color: White.

Use temperature: max +100°C

Flammability: UL94-HB flame retardant (index refers to the material).

Features: POM is characterized by good mechanical strength, high hardness and rigidity. In the table, if the P1 value coincides with the L value, the spacer has a single thread along the entire axis.

On request: these spacers can be made in intermediate lengths (even decimal), which are included between the minimum and maximum length.




fig. B




fig. C

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	specific	thread pitch F1	thread value F1	thread pitch F2	thread value F2	ØB mm	L mm	P1 mm	pack pcs.
FF01 R 3060 60	fig. TO	Metric	3	Metric	3	6	60	10	500

* Item with through hole and fully threaded.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

