









The drawing is indicative and the proportions may not correspond to the table or real dimensions.

BLOCCACAVI IN PLASTICA AD INNESTO A 90° CON PREASSEMBLAGGIO SUL CAVO -SERIE "HEYCO"

ITEM: RDD 101A-90

Codice EZ: 147511, BLOCCACAVI codice Heyco: 1816.

Material: polyamide 6/6.

Color: black.

ØG

Use temperature: -18°C / +105°C

Flammability: flame retardant and self-extinguishing UL94-V2.

Regulations and Certifications: UR. CSA.

Features: these cable clamps have good chemical resistance and good electrical properties. They offer valid electrical and mechanical protection to the cables, absorbing the traction, thrust and torsion forces that can be exerted on the cables themselves. The 90 ° bend ensures that the cable is parallel and grazing to the structure and allows you to save space. In addition, in the case of limited space, these cable clamps act as a bumper. They are distinguished by the advantage of being able to pre-assemble them on the cable (they clip on the cable) and then install them in the structure even at a later time or in a remote place, thus saving on installation costs. They can be installed in round mounting holes (ØG), but if you make a hole with the shape indicated by us in the drawing (G1) the cable clamp will not be able to rotate. To plug holes with this template, DD type "DOUBLE" plugs are available. The cable clamps are produced in two configurations: for flat cables and for round cables. Thanks to the fixing teeth, these cable clamps snap on and adapt to the thickness of the frame up to a maximum indicated in the table. For the preassembly operation on the cable it is advisable to use our RDD PLIERS or RDD PRESS tools; assembly in the structure, on the other hand, is done by hand without the aid of additional tools. On request: for quantity, they can be supplied in white or in other colors on sample.

ITEM	specific	for cables	A mm	B mm	B1 mm	B2 mm	ØG mm	G1 mm	H1 mm	frame	pack pcs.
		mm								thickness	
										mm	
RDD	for round	3,3 - 5,3	7,1	17,4	16,4	15,2	15,9	14	11,4	0,8 - 2,5	500
101A-90	cables										

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso



