



DOUBLE INSULATED POINTS

ITEM: CET-2 100 S

Codice EZ: request the code from our sales office

Material: tinned copper ferrules with polypropylene insulation.

Color: the color of the insulation varies according to the section of the conductor to be combined (see table).

Use temperature: max +105°C

Features: these ferrules are made of copper and electrolytically tinned to offer the best possible protection against corrosion. They are used in cases where the insertion of two cables is required. The inside of the "EasyEntry" type ferrules facilitates the insertion of the cable eliminating the risk of bending the wires.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	color code	section mm 2	AWG section	ØA mm	And mm	H mm	L mm	L1 mm	pack pcs.
CET-2 100 S	Brown	T.	2x10	2x8	5,8	13,3	7,5	24	12	500

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

