



INDIVIDUAL INSULATED POINTS

ITEM: CEW 015-3,8 C

Codice EZ: request the code from our sales office

Material: tinned copper ferrules with polypropylene insulation.

Color: the color of the insulation varies according to the section of the conductor to be combined (see table).

Use temperature: max +105°C

Regulations and Certifications: UL.

Features: these ferrules are made of copper and electrolytically tinned to offer the best possible protection against corrosion. They are made with dimensions in accordance with DIN 46228/4. The inside of the "EasyEntry" type ferrules facilitates the insertion of the cable eliminating the risk of bending the wires.

On request: larger sizes are available up to a maximum section of 150 mm².

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	color code	section mm ²	AWG section	ØA mm	ØA1 mm	L mm	L1 mm	pack pcs.
CEW 015-3,8 C	Red	W	1,5	16	1,7	3,8	12	6	-

* UL compliant article.

THE ITEMS FOR WHICH THE QUANTITY PER PACKAGE IS NOT SPECIFIED ARE ON REQUEST AND SUBJECT TO A MINIMUM QUANTITY AVAILABLE TO BE REQUESTED AT OUR SALES OFFICE.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

