



PRE-INSULATED MULTIPLE FASTON - "ELPRESS" SERIES -

Material: faston in tin-plated brass with PVC insulation.

Color: the color of the insulation varies according to the section of the conductor to be combined (see table).

Use temperature: max +60°C

Flammability: flame retardant and self-extinguishing UL94-V0.

Features: these fastons are made of brass and electrolytically tinned to offer the maximum possible protection against corrosion. The faston collar is reinforced with an additional brass tube that allows a perfect crimping at any point around the collar. In addition, the additional tube offers greater mechanical strength and better electrical conductivity. To facilitate identification and/or inspection, the fastons are marked, where possible, with the maximum usable conductor section. The insulation has excellent deformation characteristics such as to prevent deterioration during the crimping operation and maintains its qualities unchanged even in the presence of high temperatures.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	color Isolation	section mm 2	AWG section	for male faston / faston tongue	ØA mm	L mm	insulation material	pack pcs.
A 1507 FLSH	Red	0,5 - 1,5	20 - 16	6.3x0.8	3,2	22	PA	1000
A 2507 FLSH	blue	1,5 - 2,5	16 - 14	6.3x0.8	3,9	22	PA	1000

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

