



## PARALLEL INSULATED JOINTS - "ELPRESS" SERIES -

Material: tinned copper joints (copper 99.95%) with halogen-free polyamide (PA) insulation.

Color: the color of the insulation varies according to the section of the conductor to be combined (see table).

Use temperature: max +90°C

Flammability: flame retardant and self-extinguishing UL94-V0.

Features: these couplings are made of copper and electrolytically tinned to offer the best possible protection against corrosion. During the manufacturing phase, the inner tube is subjected to the annealing treatment in order to allow a perfect crimping at any point. The insulation has excellent deformation characteristics such as to prevent deterioration during the crimping operation and maintains its qualities unchanged even in the presence of high temperatures. To make an optimal connection with the cables, it is advisable to crimp the joints twice near the center.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	color Isolation	section mm 2	AWG section	ØA mm	L mm	insulation material	pack pcs.
A 1515 PSK	Red	0,5 - 1,5	20 - 20	3,2	17	PA	1000
A 2517 PSK	blue	1,5 - 2,5	16 - 16	4	17	PA	1000
A 4634 PSK	yellow	4 - 6	12 - 10	5,6	21	PA	1000

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

### ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

