



HEAD-HEAD INSULATED JOINTS - "ELPRESS" SERIES -

Material: joints in tinned copper (copper 99.95%) with halogen-free polycarbonate (PC) insulation.

Color: the color of the insulation varies according to the section of the conductor to be combined (see table).

Use temperature: max +100°C

Flammability: flame retardant and self-extinguishing UL94-V2.

Features: these couplings are made of copper and electrolytically tinned to offer the best possible protection against corrosion. During the manufacturing phase, the inner tube is subjected to the annealing treatment in order to allow a perfect crimping at any point. The insulation has excellent deformation characteristics such as to prevent deterioration during the crimping operation and maintains its qualities unchanged even in the presence of high temperatures. For a correct connection with the cables, these joints must be crimped on both ends.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	color Isolation	section mm 2	AWG section	ØA mm	L mm	insulation material	pack pcs.
A 0824 SK	green	0,25 - 0,75	24 - 20	2,9	24,5	PC	1000
A 1525 SK	Red	0,5 - 1,5	20 - 16	3,4	24	PC	1000
A 2527 SK	blue	1,5 - 2,5	16 - 14	4,3	26	PC	1000
A 4652 SK	yellow	4 - 6	12 - 10	6,5	33	PC	500

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

