



HEAD-HEAD INSULATED JOINTS - "EZ" SERIES -

Material: tinned copper joints with halogen-free PVC insulation.

Color: the color of the insulation varies according to the section of the conductor to be combined (see table).

Use temperature: max +60°C

Flammability: flame retardant and self-extinguishing UL94-V2.

Features: to ensure excellent surface protection and to allow perfect crimping, these joints are subjected to electrolytic tin plating and annealing treatments. For a correct connection with the cables, the couplings must be crimped on both ends.

On request: for quantity, they can be supplied with halogen-free PA 66 insulation (max +90°C).

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	color Isolation	section mm 2	AWG section	ØA mm	ØA1 mm	L mm	L1 mm	pack pcs.
F 1515 PSK PVC	Red	0,25 - 1,5	22 - 16	4,1	1,8	26	15	500
F 2517 PSK PVC	blue	1,5 - 2,5	16 - 14	4,6	2,4	26	15	1000
F 4634 PSK PVC	yellow	4 - 6	12 - 10	6,4	3,6	26	15	1000

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

