




## SCHEMA ARTICOLO

Articolo: 1040.32.96.70.205 - Codice EZ: request the code from our sales office

06/12/2025



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

| ITEM              | Gasket | thread pitch | thread value | Ø est. min - max cable mm | key mm | ØB mm | H1 mm | H2 mm | max frame thickness mm |
|-------------------|--------|--------------|--------------|---------------------------|--------|-------|-------|-------|------------------------|
| 1040.32.96.70.205 | FPM    | Metric       | 32x1.5       | 16 - 20,5                 | 36     | 39    | 6     | 28    | 5                      |

Material: testa del pressacavo in acciaio inossidabile CrNi A2 (DIN EN 1.4305 / AISI 303), corpo del pressacavo in ottone nichelato, guarnizione e O-Ring in FPM (colore verde) oppure in FKM (colore blu).

Use temperature: -40°C / +200°C

Regulations and Certifications: CE, EHEDG.

Gasket: a "fungo" corta.

IP protection: IP 68 (fino a 10 bar) / IP 69

NB: ALL THESE ITEMS ARE ON REQUEST.

Tutte le informazioni e i dati riportati sono indicativi e possono essere soggetti a variazioni senza preavviso

## ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993