



## SCHEDA ARTICOLO

Articolo: BSN-S T38.3.7 - Codice EZ: request the code from our sales office

06/12/2025



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

| ITEM                                                                                                                                                                                                                                                              | thread pitch | thread value | Ø est. min - max cable mm                                                                                                                                                                                           | key mm | H1 mm | H2 mm |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|-------|-------|
| BSN-S T38.3.7                                                                                                                                                                                                                                                     | NPT          | 3/8"         | 3 - 7                                                                                                                                                                                                               | 20     | 31,5  | 11,5  |
| Material: pressacavo in ottone nichelato, boccola lamellare in poliammide 6, guarnizione in cloroprene, O-Ring in NBR.                                                                                                                                            |              |              | Gasket: -S (per serraggio lamellare)                                                                                                                                                                                |        |       |       |
| Use temperature: -20°C / +100°C (con punte -30°C / +150°C )                                                                                                                                                                                                       |              |              | IP protection: IP 66 / IP 68 (fino a 5 bar) / IP 69, Type 1/4/4X/12/13 (UL 50E).                                                                                                                                    |        |       |       |
| Flammability: antifiama e autoestinguente UL94-V2.                                                                                                                                                                                                                |              |              | Regulations and Certifications: CE, c-UL-us (UL 514B, CSA C22.2 Nr. 18.3-12 e 94.2-15), GOST. Alcune normative potrebbero non coprire tutte le dimensioni; si prega di informarsi presso il nostro ufficio vendite. |        |       |       |
| NB: if in the table, in the "key" column, there are two dimensions separated by "/" (example: 20/24), the first dimension corresponds to the HEAD of the cable gland, while the second to the BODY. In the case of a single size, it corresponds to both parties. |              |              |                                                                                                                                                                                                                     |        |       |       |
| Tutte le informazioni e i dati riportati sono indicativi e possono essere soggetti a variazioni senza preavviso                                                                                                                                                   |              |              |                                                                                                                                                                                                                     |        |       |       |

## ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

