



## SCHEDA ARTICOLO

Articolo: BSN-S PG13.6.12 - Codice EZ: request the code from our sales office

06/12/2025



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

| ITEM                                                                                                                   | thread pitch | thread value | Ø est. min - max cable mm | key mm                                                                                                                                                                                                              | H1 mm | H2 mm |
|------------------------------------------------------------------------------------------------------------------------|--------------|--------------|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------|
| BSN-S PG13.6.12                                                                                                        | PG           | 13,5         | 6 - 12                    | 22                                                                                                                                                                                                                  | 26,5  | 6,5   |
|                                                                                                                        |              |              |                           |                                                                                                                                                                                                                     |       |       |
| Material: pressacavo in ottone nichelato, boccola lamellare in poliammide 6, guarnizione in cloroprene, O-Ring in NBR. |              |              |                           | Gasket: -S (per serraggio lamellare)                                                                                                                                                                                |       |       |
| Use temperature: -20°C / +100°C (con punte -30°C / +150°C )                                                            |              |              |                           | IP protection: IP 66 / IP 68 (fino a 5 bar) / IP 69, Type 1/4/4X/12/13 (UL 50E).                                                                                                                                    |       |       |
| Flammability: antifiama e autoestinguente UL94-V2.                                                                     |              |              |                           | Regulations and Certifications: CE, c-UL-us (UL 514B, CSA C22.2 Nr. 18.3-12 e 94.2-15), GOST. Alcune normative potrebbero non coprire tutte le dimensioni; si prega di informarsi presso il nostro ufficio vendite. |       |       |
|                                                                                                                        |              |              |                           |                                                                                                                                                                                                                     |       |       |
|                                                                                                                        |              |              |                           |                                                                                                                                                                                                                     |       |       |
|                                                                                                                        |              |              |                           |                                                                                                                                                                                                                     |       |       |
| Tutte le informazioni e i dati riportati sono indicativi e possono essere soggetti a variazioni senza preavviso        |              |              |                           |                                                                                                                                                                                                                     |       |       |

## ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

