




SCHEMA ARTICOLO

Articolo: MET-S M50.17.29 - Codice EZ: 176412

06/12/2025



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	thread pitch	thread value	Ø est. min - max cable mm	key mm	H1 mm	H2 mm
MET-S M50.17.29	Metric	50x1.5	17 - 29	55	37	9

Material: pressacavo in ottone nichelato, boccola lamellare in poliammide 6 completa di O-Ring, O-Ring in Nitrile 70 Sh A, guarnizione in EPDM.

Use temperature: -40°C / +100°C

Gasket: -S (per serraggio lamellare)

IP protection: IP 66, IP 68.

* cable gland with plastic/rubber content lower than 10 g and therefore suitable for use in the railway sector and on rail machinery. In fact, having made the necessary checks by the installer regarding the position and environment in which this item should be mounted, the railway standard EN 45545 in paragraph 4.1 provides that for products with a mass of less than 10 g no requirement is required. classification.

Tutte le informazioni e i dati riportati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

