




SCHEMA ARTICOLO

Articolo: 1045.40.230 - Codice EZ: 162725

06/12/2025



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	thread pitch	thread value	Ø est. min - max cable mm	key mm	H1 mm	H2 mm
1045.40.230	Metric	40x1.5	15 - 23	46	40	8

Material: pressacavo in ottone nichelato, inserto lamellare in Poliammide 6, guarnizione in TPE, O-ring in NBR.

Gasket: cilindrica standard.

Use temperature: -40°C / +100°C

IP protection: IP 68

Regulations and Certifications: CE, VDE, c-UR-us, DNV GL, EAC.

Tutte le informazioni e i dati riportati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

