Elektrozubehör
Cable management from E to Z

SCHEDA ARTICOLO

Articolo: BAS-MF PG42 2x16 - Codice EZ: request the code from our sales office 06/12/2025



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	thread pitch	thread value	n. holes	Ø est. min - max cable mm	key mm	H1 mm	H2 mm
BAS-MF PG42 2x16	PG	42	2	14 - 16	65/65	36,5	10

Material: pressacavo in ottone nichelato, O-Ring in nitrile 70 Sh A, guarnizione in santoprene 73 Sh A.	Gasket: -MF (a “fungo” multifilare con fori aperti).
Use temperature: -25°C / +120°C	IP protection: IP 68

* The outer cable diameter has a tolerance of ± 15%.
NB: if in the table, in the "key" column, there are two dimensions separated by “/” (example: 20/24), the first dimension corresponds to the HEAD of the cable gland, while the second to the BODY. In the case of a single dimension, it corresponds to both parties. THE ITEMS FOR WHICH THE QUANTITY PER PACKAGE IS NOT SPECIFIED ARE ON REQUEST AND SUBJECT TO A MINIMUM QUANTITY AVAILABLE TO BE REQUESTED AT OUR SALES OFFICE.

Tutte le informazioni e i dati riportati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993