



SCHEMA ARTICOLO

Articolo: 1100.48.490 - Codice EZ: request the code from our sales office

06/12/2025



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Gasket	thread pitch	thread value	Ø est. min - max cable mm	key mm	H1 mm	H2 mm
1100.48.490	-FCP	PG	48	43 - 49	65	37	15
Material: pressacavo in ottone nichelato, guarnizione in TPE, O-Ring in NBR.				Gasket: -FLP (a "fungo" lunga), -FL2P (a "fungo" lunga e a due elementi), -FCP (a "fungo" corta), -FC2P (a "fungo" corta e a due elementi).			
Use temperature: -40°C / +100°C				IP protection: IP 68 (fino a 10 bar) / IP 69			
Regulations and Certifications: c-UL-us, c-UR-us, EAC.							

Tutte le informazioni e i dati riportati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

