



SCHEMA ARTICOLO

Articolo: F1000.4.20 - Codice EZ: request the code from our sales office

06/12/2025



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	thread pitch	thread value	Ø est. min - max cable mm	key mm	H1 mm	H2 mm
F1000.4.20	Metric	20x1.5	4 - 15	24	23	6

Material: pressacavo in ottone nichelato, guarnizione in TPE modificato (colore grigio chiaro RAL 7035), O-Ring in NBR.

Use temperature: -50°C / + 105°C

Regulations and Certifications: EN 45545-2 HL3, NFPA 130.

Gasket: a "cipolla".

IP protection: IP 68 / IP 69.

NB: THESE ITEMS ARE ON REQUEST.

Tutte le informazioni e i dati riportati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

