




SCHEMA ARTICOLO

Articolo: RTC-S PG2106.9.16 - Codice EZ: 170952

06/12/2025



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	thread pitch	thread value	Ø est. min - max cable mm	key mm	H1 mm	H2 mm
RTC-S PG2106.9.16	black RAL 9005	PG	21	9 - 16	33	38,4	11

Material: pressacavo e O-Ring integrato in poliammide 6, guarnizione in cloroprene.

Gasket: -S (per serraggio lamellare).

IP protection: IP 66 / IP 68 (fino a 5 bar), Type 1/4/4X/12/13 (UL 50E).

Regulations and Certifications: CE, c-UL-us (UL 514B, CSA C22.2 Nr. 18.3-12 e 94.2-15), c-CSA-us (CSA C22.2), GOST. Alcune normative potrebbero non coprire tutte le dimensioni; si prega di informarsi presso il nostro ufficio vendite.

Color: grigio chiaro RAL 7035, grigio scuro RAL 7001, nero RAL 9005.

Use temperature: -20°C / +100°C (con punte fino a +150°C)

Flammability: antifiama e autoestinguente UL94-V2.

Tutte le informazioni e i dati riportati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

