



SCHEMA ARTICOLO

Articolo: TEC-S M2504.5.12 L - Codice EZ: request the code from our sales office

06/12/2025



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	thread pitch	thread value	Ø est. min - max cable mm	key mm	H1 mm	H2 mm
TEC-S M2504.5.12 L	gray RAL 7035	Metric	25x1.5	5 - 12	27	35	15

Material: pressacavo in poliammide 6, guarnizione in neoprene.

Gasket: -S (per serraggio lamellare).

IP protection: IP 68.

Regulations and Certifications: VDE (EN 62444), UL, c-UL-us, DNV.

Color: grigio chiaro RAL 7035, grigio scuro RAL 7001 o nero RAL 9005.

Use temperature: -40°C / +100°C

Flammability: antifiama e autoestinguente UL94-V2.

Tutte le informazioni e i dati riportati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

