



SCHEMA ARTICOLO

Articolo: GVS 2,5 KV 2,5 - Codice EZ: 113925

06/12/2025



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	specific	ØA mm
GVS 2,5 KV 2,5	sheath 2500 Volt	2,5

Material: braided fiberglass sheath covered with silicone resin.

Color: brick red.

Use temperature: -60°C / +250°C (with peaks over +290°C)

Flammability: flame retardant and self-extinguishing UL VW-1.

Regulations and Certifications: UL, IEC.

THE ITEMS FOR WHICH THE QUANTITY PER PACKAGE IS NOT SPECIFIED ARE ON REQUEST AND SUBJECT TO A MINIMUM QUANTITY AVAILABLE TO BE REQUESTED AT OUR SALES OFFICE.

Tutte le informazioni e i dati riportati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

