




SCHEMA ARTICOLO

Articolo: KOS-LT 1 LD - Codice EZ: request the code from our sales office

06/12/2025



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Ø mounting hole mm	spessore telaio min - max mm	ØB mm	H mm	H1 mm
KOS-LT 1 LD***	34,9	0,8 - 3,2	45,2	14,3	10,7

Material: santoprene (thermoplastic rubber), hardness: 85 Sh A.

Color: black.

Use temperature: -60°C / +135°C

IP protection: IP 66, Nema 4 e 4X.

Flammability: flame retardant and self-extinguishing UL94-V0.

Regulations and Certifications: UL, UR, CSA.

***Articolo in TPE più morbido con durezza 75 Sh A, a normativa UL. Per quantità, può essere fornito in colore grigio.

THE ITEMS FOR WHICH THE QUANTITY PER PACKAGE IS NOT SPECIFIED ARE ON REQUEST AND SUBJECT TO A MINIMUM QUANTITY AVAILABLE TO BE REQUESTED AT OUR SALES OFFICE.

Tutte le informazioni e i dati riportati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

