



SCHEMA ARTICOLO

Articolo: RQGKZP-M 40.20.25 AD34,5 L8 NERI - Codice EZ: request the code from our sales office



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	specific	OD tube AD	thread pitch	thread value	Ø est. min - max cable mm	ØA mm	ØB mm	F mm	H mm	key mm
RQGKZP-M 40.20.25 AD34,5 L8 NERI	RQGKZP	34,5	Metric	40x1.5	20 - 25	27,5	48	8	75	42/43

Material: fitting body in polyamide 6, internal gasket in TPE, body of the cable gland and thread in nickel-plated brass.

Color: black.

Use temperature: -50°C / +120°C

IP protection: IP 68 according to EN 60529/IEC 60529 specifications and IP 69K according to DIN 40050 T.9 specifications.

Flammability: flame retardant and self-extinguishing UL94-V0 (polyamide 6).

Regulations and Certifications: CE, VDE (EN/IEC 61386-23), DIN EN 45545-2 HL3, DIN EN 45545-3 E30 (soltanto per i raccordi RQGKZP), NFPA 130 (ASTM E162/E662, SMP 800-C), LLOYD'S REGISTER (soltanto per i raccordi RQGKZ), c-UR-us (UL 1696 / CSA 22.2; file n. E86359, per le misure AD13-AD54,5), JRMA.

N.B.: se in tabella, nella colonna "chiave", vi sono due dimensioni separate da " / " (esempio: 22/17), la prima dimensione corrisponde al CORPO del raccordo, mentre la seconda alla TESTA filettata. In caso di dimensione unica, essa corrisponde ad entrambe le parti.

Tutte le informazioni e i dati riportati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

