




SCHEDA ARTICOLO

Articolo: DRC 07,9A - Codice EZ: request the code from our sales office

06/12/2025



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	Material	H mm	super thick frame. / infer.	Top mounting hole ø mm	Lower mounting hole ø mm
DRC 07,9A**	White	PA 66-V0	7,9	2,4 / 0,8-2	4	4,8

Material: UL94-V2 flame-retardant polyamide 66 (PA 66-V2) and UL94-V0 flame-retardant polyamide 66 (PA 66-V0)	Color: natural (PA 66-V2), white (PA 66-V0).
Use temperature: max +85°C (PA 66-V2), max +105°C (PA 66-V0).	Flammability: flame-retardant and self-extinguishing UL94-V2 (PA 66-V2), flame-retardant and self-extinguishing UL94-V0 (PA 66-V0).

* These spacers can be supplied with the same dimensions, but for less than 0.2-1.4mm wall thickness. Furthermore, they can also be supplied in metric sizes, i.e. with the following heights (A): 6, 8, 10, 12, 14, 16 mm. ** These spacers can be supplied with the same dimensions, but for wall thicknesses of less than 2-3.6mm.

Tutte le informazioni e i dati riportati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

